AntTec Group Co,Ltd

Glass Surface Infrared Panel Heater



Technical Details	
Controls	 Digitally controlled eletronic thermostat(5-40°C) Clear LCD dispaly 433 wireless remote control App control weekly program open window detection
Construction	Tempered glass and aluminum construction innovation design, no frame
Element	Long life carbon crystal heating element4 tiers PET, total 0.8mm thickness
Installation	Strong mounting brackets for easy fixing
Safe	 thermal cut-out ,auto reset type overheat detection
IP rating	IP24
Supply	1.8 metre fitted;3X1.0H05RN-FClass 1,with earth wire!
Colour/finish	white,black,mirror

Warranty & Approvals		
Approvals	CE UKCA ROHS	
Warranty	2 Years	


Product Description

Infrared heaters are more energy-efficient than other space heaters as they do not heat up the entire room. Convection heaters heat the air and air circulation can cause a significant loss of heat. As soon as doors are opened or briefly ventilated, the room temperature drops. Infrared heaters instead heat matter, such as people, furniture and walls. These then release heat back into the room over time. With an infrared heater you do not have to heat the entire room, but can create heated zones and direct the heat to specific areas while allowing the air to remain cool and fresh.

Key Features

- Four panel heater outputs 320W 450W 580W 700W
- · Contracted design, Clear LCD dispaly
- 433 wireless remote control
- · APP control power by TUYA.
- · Long life Carbon crystal eating element
- Energy efficient low energy costs, electric conversion efficiency 98%
- · Draught and Noise free
- Can be Ceiling , Wall Mounted or free stand.
- IP24 Protection

Details&Dimensions





GCB32

320

60

4.5

60

70

70

8

750

1600

1900

Model

Power (w)

Long(CM)

Width(CM)

High(CM)

Weight(kg)

Long(CM)

Width(CM)
High(CM)

Weight(kg)

Container loading(20)

Container loading(40)

Container

loading(40HQ)



Mounting bracket

GCB58

1040

1200

GCB45

450

80

4.5

60

9

90

70

10

590

1250

1500

Packaging details



580 700 100 120 4.5 4.5 60 60 11 13 110 130 70 70 12 15 480 400

880

1040

GCB70